NETWORK

Data sheet: LN-307

Product code	:	LN-307
Product name	:	Network Parallel Printer Server
EAN code	:	8716502005178
Qty. masterpack / carton	:	5/10

Product weight	:	500 gr.
Product dimensions	:	82(W) x 57 (D) x 25mm (H)
Gift box weight	:	680 gr.
Gift box dimensions	:	210 (W) x 70,5 (D) x 146,5 mm (H)
Masterpack weight	:	4.4 Kg.
Masterpack dimensions	:	33,5(W) x 19 (D) x 26 cm (H)
Carton weight	:	8,8 Kg.
Carton dimensions	:	40 (W) x 36 (D) x 27 cm (H)

This Network Printer Server makes it possible for you to add a parallel printer to your network simply and quickly. This printer can then be used by any user from different computers in the network. The Network Printer Server is fitted with a net work port (10/100 Mbps) so that you can connect it to any network device such as a hub, switch or a network card. Thanks to the supplied Wizard, the printer server is easy to install and because it supports the most important protocols, the printer server can be easily integrated in almost any network.

Box content:

- Network Parallel Printer Server
- User manual
- Driver CD
- Power adapter

System requirements:

- Windows 98SE/ME/2000/XP
- Parallel printer
- Free network port on Hub,
- Switch or PC

NETWORK

Data sheet: LN-307

Key features:

- Share one parallel printer between several users
- Works under the TCP/IP, IPX/SPX, NetBEUI protocols
- BiAdmin programme for confi guration/management
- Automatic IP setting
- Supports Internet Printing Protocol

Technical specifications:

- Network Interface: 10BaseT/100BaseTx,
- Auto-sensing
- Printer Connection
- IEEE1284 compliant (Nibble/Byte mode support). Type B Centronics
- Protocol Support
  - TCP/IP
  - NetBEUI
  - AppleTalk, IPX/SPX
- NOS Support
  - Windows 95/98/2000/NT/Me/XP
  - Macintosh (OS 9.x and higher)
  - UNIX, Netware 3.x/4.x/5.x

Printing methods

- PTP (Peer-to-Peer) over TCP/IP or NetBEUI protocol
- Windows LPD printing,
- SMB printing (via NetBEUI or TCP/IP protocol)
- IPP (Internet Printing Protocol),
- Macintosh LaserWriter Chooser (EtherTalk)
- NetWare NDPS LPR Printing, NetWare 3.1x (Bindery mode), 4.x (Bindery and NDS mode), 5.0 (Bindery, NDS, and NDPS in legacy mode)

- Management Tools
- BiAdmin (Windows Application)
- Web-based management (HTTP)
- PC-based SNMP applications: FTP, Telenet
- LED
  - -10BaseT, 100BaseTx,
  - Status
  - Error
- Diagnostic button - Diagnostic Printing & Reset to Factory Default
- Power Supply - 9V/500mA
- Emission -FCC / CE / VCCI/C-Tick